

---

# **tld Documentation**

***Release 0.4***

**Artur Barseghyan <artur.barseghyan@gmail.com>**

December 10, 2013



---

## **Contents**

---



Extracts the top level domain (TLD) from the URL given. List of TLD names is taken from Mozilla [http://mxr.mozilla.org/mozilla/source/netwerk/dns/src/effective\\_tld\\_names.dat?raw=1](http://mxr.mozilla.org/mozilla/source/netwerk/dns/src/effective_tld_names.dat?raw=1)

Optionally raises exceptions on non-existing TLDs or silently fails (if *fail\_silently* argument is set to True). Knows about active and inactive TLDs. If only active TLDs shall be matched against, *active\_only* argument shall be set to True (default - False).



# Installation

---

Latest stable version on PyPI:

```
$ pip install tld
```

Latest development version:

```
$ pip install -e hg+http://bitbucket.org/barseghyanartur/tld#egg=tld
```



# Usage example

---

To get the top level domain name from the URL given:

```
>>> from tld import get_tld
>>> print get_tld("http://www.google.co.uk")
'google.co.uk'
>>> print get_tld("http://www.google.idontexist", fail_silently=True)
None
```

To update-sync the tld names with the most recent version run the following from your terminal:

\$ python tld/update.py

or simply do:

```
>>> from tld.utils import update_tld_names
>>> update_tld_names()
```

## 2.1 utils Module

`tld.utils.update_tld_names(fail_silently=False)`

Updates the local copy of TLDs file.

**Parameters** `fail_silently (bool)` – If set to True, no exceptions is raised on failure but boolean False returned.

**Return bool** True on success, False on failure.

`tld.utils.get_tld(url, active_only=False, fail_silently=False)`

Extracts the top level domain based on the mozilla's effective TLD names dat file. Returns a string. May throw `TldBadUrl` or `TldDomainNotFound` exceptions if there's bad URL provided or no TLD match found respectively.

**Parameters**

- `url` – URL to get top level domain from.
- `active_only` – If set to True, only active patterns are matched.
- `fail_silently` – If set to True, no exceptions are raised and None is returned on failure.

**Returns** String with top level domain or None on failure.



# Indices and tables

---

- *genindex*
- *modindex*
- *search*



---

# Python Module Index

---

t

tld.utils, ??